

## LIST OF OUR END USER CUSTOMERS

### AUTO END CUSTOMERS



### PANEL & SWITCH BOARD END CUSTOMERS



### APPLIANCES END CUSTOMERS



We are,  
**ONE for ALL**

Estd. 02-04-1997

**SRINI LINK**  
**WIRES & CABLES**



**Srini Link** are the best twisted-pair cables in the market for transmitting data over local area Networks (LANs).

As streaming video and multimedia over LAN are gaining popularity, users demand faster data transmission and reduced waiting time. **Srini Link** cables are ideal for simple, cost-effective and high-speed transmission performance. They support a higher signal-to-noise ratio, providing better reliability for current applications and higher data rates for future applications.



**Regd. Office :**  
Plot No. 1308/2, 1308/1 & 1309/2 , G.I.D.C.,  
Phase III, Umbergaon - 396171, Dist. Valsad,  
Gujarat, INDIA.  
Tel.: +91 260 2562712 Web.: www.srinilink.com  
+91 260 2564197 Email: srinilink@srinilink.com  
Fax.: +91 260 2561789 sl.sales@srinilink.com

**Maharashtra Depot :**  
Survery No. 527/1 & 527/4,  
302 Siddhi Vinayak Bldg. - A,  
Tal. Dahanu, Bordi 401701,  
Maharashtra, INDIA.  
M.: +91 93770 12253  
E.: srinilink@srinilink.com

**Surat Depot :**  
Plot No. 15-B, Ground Floor,  
Road No.3, Opp. Dharti Namkin,  
Udhana 394210, Surat,  
Gujarat, INDIA.  
T.: +91 261 2279003  
E.: sl.suratdepot@srinilink.com

**TELEPHONE CABLE  
CAT 5e & CAT 6 CABLE**



### TELEPHONE CABLES

**Application:** These cables are specially designed for telecommunication and switchboard where very low frequency and high communication is required. These cables are mainly used in high-rise building, hotels, residential complexes, co-operate office, factories as a switchboard and internal telephone cables.

**Conductor:** With Bright-annealed EC grade copper with **99.97 % purity**, which offer low conductor resistance, lower heating and save the power consumption.

**RoHS Insulation :** Its insulation material is HDPE (High Density polyethylene) because of which  $\pm$  temperature, insulation resistance, impedance, capacitance required nominal properties are maintained.

The RoHS FR PVC sheath is loosely jacketed (coated just like sleeve) for better usage in application and usually in grey colour or as per customer requirement.

Inner Core Structure: The cores are uniformly twisted together with suitable lays & bunched together in such a way that the crosstalk get reduce.

CONDUCTOR SIZE	0.40, 0.50 & 0.60 mm & As per requirement
INSULATION THICKNESS	Average 0.20 mm
DIAMETER OF INSULATION	Maximum 0.92 mm
RIP CORD	Nylon
PACKING	100 Mtrs & As per requirement



### TECHNICAL SPECIFICATION :

Construction & Outer diameter	1 Pair 2.75 mm	2 Pair 3.50 mm	3 Pair 4.00 mm	4 Pair 4.70 mm	5 Pair 5.50 mm	10 Pair 8.20 mm	20 Pair 10.50 mm
1 Pair	White-Blue	White-Blue	White-Blue	White-Blue	White-Blue	White-Blue	White-Blue
2 Pair	-	White-Orange	White-Orange	White-Orange	White-Orange	White-Orange	White-Orange
3 Pair	-	-	White-Green	White-Green	White-Green	White-Green	White-Green
4 Pair	-	-	-	White-Brown	White-Brown	White-Brown	White-Brown
5 Pair	-	-	-	-	White-Grey	White-Grey	White-Grey
6 Pair	-	-	-	-	-	Red-Blue	Red-Blue
7 Pair	-	-	-	-	-	Red-Orange	Red-Orange
8 Pair	-	-	-	-	-	Red-Green	Red-Green
9 Pair	-	-	-	-	-	Red-Brown	Red-Brown
10 Pair	-	-	-	-	-	Red-Grey	Red-Grey
11 Pair	-	-	-	-	-	-	Black-Blue
12 Pair	-	-	-	-	-	-	Black-Orange
13 Pair	-	-	-	-	-	-	Black-Green
14 Pair	-	-	-	-	-	-	Black-Brown
15 Pair	-	-	-	-	-	-	Black-Grey
16 Pair	-	-	-	-	-	-	Yellow-Blue
17 Pair	-	-	-	-	-	-	Yellow-Orange
18 Pair	-	-	-	-	-	-	Yellow-Green
19 Pair	-	-	-	-	-	-	Yellow-Brown
20 Pair	-	-	-	-	-	-	Yellow-Grey



### CAT 5e & CAT 6

**Application:** Ethernet cables are mainly used in Local Area Networking (LAN) cable system, in normal terms internet connection, grouping of more than one computers.

CAT 5e cables are used where function is up to 100 MHz & data transfer rate upto 100 Mbps is required

CAT 6 cables are used where function is up to 250 MHz & data transfer rate upto 1000 Mbps is required

**Conductor:** With Bright-annealed EC grade copper with **99.97 % purity**, which offer low conductor resistance, lower heating and save the power consumption.

**RoHS Insulation & Sheath :** Its insulation material is HDPE (High Density polyethylene) because of which  $\pm$  temperature, insulation resistance, impedance, capacitance required nominal properties are maintained.

As it is outdoor & indoor cable its Sheathing is done with special grade FR, FRLS with ultraviolet protective PVC Compound which make Sheath tough & hard with good abrasion resistance, which results in long life.

SPECIFICATION	TIA/EIA 568B, ISO 11801, EN 50169, EN 50173, IEEE 802.3 – IEEE 802.5, CDDI			
SIZE	CAT 5e	24 AWG,	0.205 Sq.mm,	0.50 mm
	CAT 6	23 AWG,	0.254 Sq.mm,	0.57 mm
Packing	305 Mtrs or As per requirement			

Construction	Cat 5 (4 Pairs)	Cat 6 (4 Pairs)
Insulation & Sheath diameter	1.0 $\pm$ 0.05 mm & 5.10 + 0.02 mm	1.0 $\pm$ 0.05 mm & 5.40 + 0.02 mm
1 Pair	White/Blue - Blue	
2 Pair	White/Orange - Orange	
3 Pair	White/Green - Green	
4 Pair	White/Brown - Brown	

### CABLE PROPERTIES

Min. Installation Bend Radius	8 x Dia
Min. Installed Bending Radius	4 x Dia
Max. Installation Tension	100 N
Max. Installed Tension	Zero
Installation Temp. Range (Installed)	0 to 50° C
Operating Temp. Range	-20 to 70° C

### ELECTRICAL CHARACTERISTICS @ 20 °C

Characteristic Impedance	100 $\pm$ 6 $\Omega$
Conductor Resistance	$\leq$ 9.38 $\Omega$ / 100m
Insulation Resistance	100 M $\Omega$
Mutual Capacitance	< 5.6nf/100m
Resistance Unbalance	5% Max
Capacitance Unbalance	330pF/100m
Delay Skew	< 45nS
NVP (%)	72V
Operating Voltage	1.0KV dc or 0.75KV ac
Dielectric Strength	for 1min

